



# ESTIMATOR SHEET

Please be advised that these numbers will vary depending on many factors, such as existing surface texture and its porosity. Use these numbers as a general guideline. These numbers account for a Bond Coat, Scratch Coat, and Texture Coat. Two coats of sealer are suggested for every application (the amount allows for two coats.)

**\*\* A bond and scratch coat are recommended on all applications! \*\***

Let the square footage of the job be your guide.

For example, if a job is **1300 sq. ft.**, simply add the columns of each product in the 300 and 1000 column.

So, **Additive** is 7 + 22 = 29 gallons. **Aggregate** is 4 + 11 = 15 bags. **Top Coat** is 3 + 10 = 13 gallons.

## LACE TEXTURE

Job Sq. Ft.	100	200	300	400	500	600	700	800	900	1000
Gallons of <b>Acrylic Additive</b>	3	5	7	9	11	14	16	18	20	22
# of 50 lb. bags of <b>Aggregate</b>	2	3	4	5	6	7	8	9	10	11
Gallons of <b>Top Coat</b>	1	2	3	4	5	6	7	8	9	10

## FLAGSTONE & SALTILLO TEXTURES - (Not stamped)

Job Sq. Ft.	100	200	300	400	500	600	700	800	900	1000
Gallons of <b>Acrylic Additive</b>	3	6	9	12	15	18	21	24	27	30
# of 50 lb. bags of <b>Aggregate</b>	2	3	5	6	8	9	11	12	14	15

To obtain the color of your choice, use **Powder Colorants**, **Decorative Stains**, or diluted **Top Coat** (up to 10 parts water to one part Top Coat).

Gallons <b>Clear Sealer</b>	½	1	1 ½	2	2 ½	3	3 ½	4	4 ½	5
--------------------------------	---	---	-----	---	-----	---	-----	---	-----	---



## STAMP OVERLAY

*Use regular Aggregate for the Scratch Coat. Use Stamp Overlay Aggregate for the texture coat.*

Job Sq. Ft.	100	200	300	400	500	600	700	800	900	1000
Gallons of <b>Acrylic Additive</b>	9	15	21	27	33	40	48	55	60	70
# of 50 lb. bags of <b>Aggregate</b> (regular aggregate – for Scratch Coat only)	½	1	1 ½	2	2 ½	3	3 ½	4	4 ½	5
# of 50 lb. bags of <b>Overlay Aggregate</b> (Texture Coat)	4	8	12	16	20	24	28	32	36	40
Gallons of <b>Bubble Gum Release</b>	½	1	1 ½	2	2 ½	3	3 ½	4	4 ½	5
To obtain the color of your choice, use <b>Powder Colorants, Decorative Stains</b> , or diluted <b>Top Coat</b> (up to 10 parts water to one part Top Coat).										
Gallons <b>Clear Sealer</b>	½	1	1 ½	2	2 ½	3	3 ½	4	4 ½	5

If you have any application questions, please do not hesitate to call us at 888.440.3320 or email us at [info@prefdeck.com](mailto:info@prefdeck.com). Visit our website at [www.prefdeck.com](http://www.prefdeck.com).

**Do not apply any Preferred Deck products when the deck temperature is less than 50 degrees.** We suggest using an infrared temperature gun, which can be purchased at most auto parts stores.

Preferred Deck Systems  
7534 W. Madison St.  
Tolleson, AZ 85353  
888.440.3320  
[www.prefdeck.com](http://www.prefdeck.com)