



7534 W. Madison St.
Tolleson, AZ 85353
Ph – 888.440.3320
Fax – 623.474.2251
www.prefdeck.com
info@prefdeck.com

MATERIAL SAFETY DATA SHEET

PREFERRED EPOXY – Finish Wax

Product Class: Mixture

HMS Codes: H F R P
1 0 0

SECTION I – MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: PREFERRED DECK SYSTEMS LLC
ADDRESS: 7534 W. MADISON ST.
TOLLESON, AZ 85353

EMERGENCY PHONE: (602) 909-6199 or (602) 361-8100
INFORMATION PHONE: (888) 440-3320
DATE PRINTED: 11/10/09
NAME OF PREPARER: RUSTY GONZALES

24 HOUR EMERGENCY ASSISTANCE: Chemtrec 1-800-424-9300

SECTION II – HAZARDS INGREDIENTS

<u>REPORTABLE COMPONENTS</u>	<u>CAS#</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Glyco Ethers	(111-77-3) & 9111-90-0)	N/E	N/E
GlycolEther DPM	34590-94-8	N/E	100 ppm skin
Ammonium hydroxide	1336-21-6	N/E	50 ppm

SECTION III – PHYSICAL DATA

Boiling Point: N/E
Vapor Pressure: N/E
Vapor Density: >1
Specific Gravity: 1.03
Percent Volatiles: ~80
Solubility in Water: Miscible
Evaporation Rate: ~1
Appearance: Milky white liquid.
Odor: slight odor
PH: 8-9

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

Flash Point: (Test Method) >200°F: (TCC)
Flammable Limits: % Volume in Air LEL: N/E UEL: N/E
Extinguishing media: Same as suitable for the surrounding materials
Hazardous Combustion Products: Carbon Monoxide, Carbon Dioxide
Special Fire Fighting Procedures: Toxic gasses may be released during decomposition at high temperatures. Use self contained breathing apparatus.
Fire and Explosion Hazards: None Known

SECTION V – REACTIVITY DATA

Stability: Stable
Hazardous Polymerization: Will not occur
Incompatibility: N/A
Conditions to avoid: Temperature above 120°F (49°C) and below freezing
Conditions to avoid: N/A
Materials to avoid: Strong oxidizing agents, acids and alkali's.

MATERIAL SAFETY DATA SHEET

PREFERRED EPOXY – Finish Wax

===== SECTION VI –HEALTH HAZARD DATA =====

Medical conditions aggravated by exposure: None Known
Primary Route of Entry: Dermal.
Eye Contact: Irritation, forms film that may stick eyelids together.
Skin Contact: Possible irritation.
Ingestion: Stomach upset, nausea
Inhalation: No known effects

===== SECTION VII – EMERGENCY FIRST AID PROCEDURES =====

Eyes: Flush thoroughly with water, lifting both eyelids. If irritation persists, seek medical help
Skin: Wash with soap and water, Remove contaminated clothing and launder before reuse
Ingestion. Drink several glasses of water to dilute the product. Induce vomiting if directed to so by doctor or poison control center. Do not give liquids to an unconscious person. Get immediate medical help.

===== SECTION VIII – SPECIAL PROTECTION INFORMATION =====

Respiratory Protection: Not Required
Ventilation: General Mechanical
Eye Protection: Recommended
Skin Protection: Rubber Gloves
Hygienic Practices in handling and storage: Wash hands after handling. Do not contaminate food or feedstuff.

===== SECTION IX – SPILL OR LEAK PROCEDURES =====

Steps to be taken if material is released or spilled: *Small spills;* Flush to sewer with large quantities of water.
Large spills; soak up on absorbent material and dispose of as non-hazardous waste.
Waste Disposal Method: Observe all local and federal regulations

===== SECTION X – SHIPPING DATA =====

D.O.T. Shipping Name:	UN/NA Number:
Technical Shipping Name:	Reportable Quantity:
D.O.T. Hazard Class:	D.O.T. Labels Required:
Freight Class:	

===== SECTION XI – DISCLAIMER =====

TO THE BEST OF OUR KNOWLEDGE THIS INFORMATION IS ACCURATE. HOWEVER, WE DO NOT GUARANTEE ITS ACCURACY AND CANNOT BE LIABLE FOW ANY DAMAGES ACTUAL OR CONSEQUENTIAL WHICH MIGHT FROM RELIANCE THEREON. IF YOU HAVE ANY QUESTIONS REGARDING THIS PRODUCT, PLEASE CONTACT PREFERRED DECK SYSTEMS AT 888.440.3320 AS SOON AS POSSIBLE.