



7534 W. Madison St.
Tolleson, AZ 85353
Ph – 888.440.3320
Fax – 623.474.2251
www.prefdeck.com
info@prefdeck.com

MATERIAL SAFETY DATA SHEET

CLEAR COAT SEALER

Page: 1

PRODUCT NAME: CLEAR COAT SEALER

HMIS CODES: H F R

===== SECTION I – MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: PREFERRED DECK SYSTEMS LLC
ADDRESS: 7534 W. MADISON ST.
TOLLESON, AZ 85353

EMERGENCY PHONE: (602) 909-6199
INFORMATION PHONE: (888) 440-3320

DATE PRINTED: 02/17/04
NAME OF PREPARER: RALPH SKAGGS

===== SECTION II – HAZARDOUS INGREDIENTS/ SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mmHg @ TEMP	WEIGHT PERCENT
* ETHYLENE GLYCOL MONOBUTYL ETHER NIOSH: TWA = 25.0 PPM, STEL = NOT ESTABLISHED, CEILING = NOT ESTABLISHED OSHA: PEL = 25.0 PPM, STEL = NOT ESTABLISHED, CEILING = NOT ESTABLISHED IDLH = 700.0 PPM	0000111-76-2	.88 77.0 F	7

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.
N/A

===== SECTION III – PHYSICAL/ CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 336.0 F
VAPOR DENSITY: HEAVIER THAN AIR
COATING V.O.C.: 1.79 lb/ gal
SOLUBILITY IN WATER: DILUTABLE
APPEARANCE AND ODOR: VISCOUS WHITE OR COLORED OPAQUE LIQUID HAVING A MILD ODOR

SPECIFIC GRAVITY (H2O=1): 1.06
EVAPORATION RATE: SLOWER THAN ETHER
MATERIAL V.O.C.: 0.94 lb/ gal

===== SECTION IV – FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: 150.0 F
FLAMMABLE LIMITS IN AIR BY VOLUME-

METHOD USED:
LOWER: 01.1% **UPPER:** 10.6%

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, AND WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

WEAR SELF CONTAINED BREATHING APPARATUS TO AVOID INHALATION OF SMOKE AND VAPORS

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS CAN RUPTURE WHEN EXPOSED TO EXTREME HEAT

MATERIAL SAFETY DATA SHEET

CLEAR SEALER

Page: 2

MATERIAL CAN SPLATTER AT TEMPERATURES ABOVE 212 F.

===== **SECTION V – REACTIVITY DATA** =====

STABILITY: STABLE
CONDITIONS TO AVOID
EXCESSIVE HEAT OR FREEZING

INCOMPATIBILITY (MATERIALS TO AVOID)
MATERIALS WHICH ARE WATER REACTIVE, STRONG ALKALINE, OR STRONG ACIDIC

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
AFTER EVAPORATION OF WATER, POLYMER CAN BURN AND PRODUCE CARBON MONOXIDE AND CARBON DIOXIDE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== **SECTION VI – HEALTH HAZARD DATA** =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
HEADACHE, NAUSEA, AND IRRITATION OF NOSE, THROAT, AND LUNGS

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE
IRRITATION OF SKIN AND EYES

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
NONE RECOGNIZED

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
MATERIAL CAN BE HARMFUL IF INGESTED

NAUSEA, DIARRHEA, AND GASTROINTESTINAL IRRITATION

HEALTH HAZARDS (ACUTE AND CHRONIC)
NONE RECOGNIZED

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No
N/A

MEDICAL CONDITIONS GENERALLY AGGREVATED BY EXPOSURE
RESPIRATORY CONDITIONS, HEADACHES, NAUSEA, AND DIZZINESS

EMERGENCY AND FIRST AID PROCEDURES
INGESTION: OBTAIN MEDICAL ATTENTION AT ONCE

EYE CONTACT: FLUSH WITH CLEAN WATER FOR FIFTEEN MINUTES AND OBTAIN MEDICAL ATTENTION

INHALATION: REMOVE TO FRESH AIR AND OBTAIN MEDICAL ATTENTION

SKIN CONTACT: WASH WITH SOAP AND WATER. OBTAIN MEDICAL ATTENTION IF IRRITATION IS SEVERE OR PERSISTENT

===== **SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE** =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

IMMEDIATELY SOAK UP SPILL WITH ABSORBANT MATERIAL SUCH AS RAGS, CLAY, SAND, ETC.

LARGE SPILLS SHOULD BE DIKED AND TRANSFERRED TO A SAFE CONTAINER

WASTE DISPOSAL METHOD

DISPOSE OF WASTE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

DO NOT DROP OR PUNCTURE CONTAINER

DO NOT EXPOSE TO FREEZING TEMPERATURE

DO NOT EXPOSE TO HIGH TEMPERATURE

OTHER PRECAUTIONS

NONE RECOGNIZED

===== **SECTION VIII – CONTROL MEASURES** =====

REPIRATORY PROTECTION

USE OF A NIOSH APPROVED CARTRIDGE RESPIRATOR IS RECOMMENDED

USE OF A SELF-CONTAINED BREATHING APPARATUS IS RECOMMENDED WHEN VENTILATION IS POOR OR LIMITED

VENTILATION

LOCAL EXHAUST AND GOOD GENERAL VENTILATION RECOMMENDED

PROTECTIVE GLOVES

CHEMICAL RESISTANT PLASTIC OR RUBBER GLOVES

EYE PROTECTION

SAFEY GOGGLES

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

IMPERVIOUS CLOTHING SUFFICIENT TO PREVENT SKIN CONTACT

WORK/ HYGIENIC PRACTICES

AVAILABILITY OF SOAP AND CLEAN WATER FOR WASHING AND EYE FLUSH

AVAILABILITY OF CLEAN CHANGE OF CLOTHS

AVAILABILITY OF BARRIER CREAMS AND LOTIONS

===== **SECTION IX – DISCLAIMER** =====

TO THE BEST OF OUR KNOWLEDGE THIS INFORMATION IS ACCURATE. HOWEVER, WE DO NOT GUARANTEE ITS ACCURACY AND CANNOT BE LIABLE FOR ANY DAMAGES ACTUAL OR CONSEQUENTIAL WHICH MIGHT FROM RELIANCE THEREON.