



7534 W Madison St
Tolleson AZ 85353
888.440.3320
www.prefdeck.com
info@prefdeck.com

MATERIAL SAFETY DATA SHEET

EFF REDUCER

Page: 1

PRODUCT NAME: EFF REDUCER

HMIS CODES: **H F R P**
0 1 0 X

===== SECTION I – MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: PREFERRED DECK SYSTEMS LLC
ADDRESS: 7534 W MADISON ST
TOLLESON AZ 85353

EMERGENCY PHONE: (602) 909-6199, (602) 361-8100 DATE PRINTED: 8/11/08
INFORMATION PHONE: 888-440-3320 NAME OF PREPARER: RUSTY GONZALES

===== SECTION II – HAZARDOUS IDENTIFICATION =====

PRIMARY ROUTES OF EXPOSURE: Inhalation. Ingestion. Skin Absorption.
EYE CONTACT: None known.
SKIN CONTACT: None known.
ACUTE INGESTION: None known.
INHALATION EFFECTS: None known.
OTHER EFFECTS: None known.

This product contains ingredients that may contribute to the following potential chronic health risks:
See Section 11 for toxicological information about Mutagens, Teratogens and Carcinogens.

===== SECTION III – COMPOSITION/ INFORMATION ON HAZARDOUS INGREDIENTS =====

There are no hazardous components per OSHA guidelines.

===== SECTION IV – FIRST AID MEASURES =====

Inhalation: If affected by inhalation, move victim to fresh air. If symptoms persist, seek medical attention.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

Skin Contact: In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. If irritation persists get medical attention.

Ingestion: If swallowed, contact medical personnel immediately to determine best course of action.

Medical Conditions Aggravated By Exposure: Any respiratory or skin condition.

===== **SECTION V – FIRE FIGHTING MEASURES** =====

Flash Point (Fahrenheit): 212° F (100° C) TCC/PM
Lower Explosive Limit: Not available. %
Upper Explosive Limit: Not available. %
Auto Ignition Temperature: Not determined. ° F (° C)
Sensitivity To Impact: No.
Sensitivity To Static Discharge: Not typically sensitive to static discharge hazards. Please see bonding and grounding information in Section 7.
Hazardous Combustion Products: See Section 10.

Unusual Fire and Explosion Hazards:
None known.

Extinguishing Media:
Carbon dioxide, dry chemical, foam and/or water fog.

Fire Fighting Procedures:
Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Use water spray to cool nearby containers and structures exposed to fire. Will not sustain combustion.

===== **SECTION VI – ACCIDENTAL RELEASE MEASURES** =====

Action to be taken if material is released or spilled:
Ventilate the area. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local/ federal regulations (see Section 13.) Avoid contact with eyes.

===== **SECTION VII – HANDLING AND STORAGE** =====

Precautions to be taken in handling and storage:
Keep away from heat, sparks, and flames. Keep container closed when not in use. Do not freeze. Do not store above 120° F (49° C.) Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA Regulation 910.106, Ontario OH&S Regulation 851 Section 22. Empty containers may contain product residue, including flammable or explosive vapors. All label warnings must be observed until the container has been commercially cleaned or reconditioned. Do not cut, drill, grind, or weld on or near container. Do not puncture container. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

===== **SECTION VIII – PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS** =====

Personal Protective Equipment

Eye and Face Protection:
Wear safety glasses or goggles to protect against exposure.

Skin Protection:
Usual hand protection recommended for handling resin products. Usual clothing for handling resin products.

MATERIAL SAFETY DATA SHEET

EFF REDUCER

Page: 3

Respiratory Protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air-purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

Ventilation

Ensure adequate ventilation while handling or applying in a confined area. Ventilation equipment should be explosion-proof.

Exposure Guidelines

OSHA Permissible Exposure Limits (PEL's)

ACGIH Threshold Limit Value (TLV's)

===== SECTION IX – PHYSICAL PROPERTIES =====

Odor:	Normal for this product type.
Physical State:	Liquid
pH:	Not determined.
Vapor Pressure:	24 mmHG @ 68° F (20° C)
Vapor Density (air = 1.0):	.6
Boiling Point:	212° F (100° C)
Solubility in Water:	Soluble
Coefficient of Water/ Oil Distribution:	Not determined.
Density (lbs per iS gallon):	8.8
Specific Gravity:	1.05
Evaporation Rate (butyl acetate = 1.0):	.4

===== SECTION X – STABILITY AND REACTIVITY =====

Stability:	Stable under normal conditions
Conditions to Avoid:	None known.
Incompatibility:	Avoid water-reactive materials, heat or contact with peroxides or other catalysts.
Hazardous Polymerization:	None anticipated.
Hazardous Decomposition Products:	Carbon monoxide and carbon dioxide.
Sensitivity to static discharge:	Not typically sensitive to static discharge hazards. Please see bonding and grounding information in Section 7.

===== SECTION XI – TOXICOLOGICAL INFORMATION =====

Mutagens/ Teratogens/ Carcinogens: None known.

===== SECTION XII – ECOLOGICAL DATA =====

No information on ecology is available.

===== SECTION XIII – DISPOSAL CONSIDERATIONS =====

Disposal should be made in accordance with federal, state and local regulations.

MATERIAL SAFETY DATA SHEET

EFF REDUCER

Page: 4

===== SECTION XIV – TRANSPORTATION INFORMATION =====

U.S. Department of Transportation

Proper Shipping Name: RESIN, NOT REGULATED
UN ID Number: NRRESN

49 CFR Hazardous Material Regulations Parts 100-180

The supplier will apply the combustible liquid exception in 49 CFR 173.150(f), limited quantity or "does not sustain combustion" exceptions and consumer commodity rules, when authorized. Please check 49 CFR Parts 100-180 to determine if the use of these exceptions applies to your shipments when re-shipping our products.

International Air Transport Association:

Proper Shipping Name: RESIN SOLUTION
UN ID Number: NRRESN

International Maritime Organization:

Proper Shipping Name: RESIN SOLUTION
Non-Bulk UN ID Number: NRRESN

===== SECTION XV – REGULATORY INFORMATION =====

U.S. FEDERAL REGULATIONS:

SARA 311/312 Hazard Class:

Acute: No
Chronic: No
Flammability: Yes
Reactivity: No
Sudden Pressure: No

U.S. STATE REGULATIONS:

Pennsylvania Right To Know:

Additional Non-Hazardous Materials

WATER, DEIONIZED 7732-18-5
PROPRIETARY RESIN Trade Secret

Rule 66 status of product: Not photo-chemically reactive.

INTERNATIONAL REGULATIONS - Chemical Inventories

TSCA Inventory:

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List:

All components of this product are listed on the Domestic Substances List.

MATERIAL SAFETY DATA SHEET

EFF REDUCER

Page: 5

===== SECTION XVI – OTHER INFORMATION =====

HMIS Codes

Health: 0
Flammability: 1
Reactivity: 0
PPE: X - See Section 8 for Personal Protective Equipment (PPE).

Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

===== SECTION XVII – DISCLAIMER =====

TO THE BEST OF OUR KNOWLEDGE THIS INFORMATION IS ACCURATE. HOWEVER WE DO NOT GUARANTEE ITS ACCURACY AND CANNOT BE LIABLE FOR ANY DAMAGES ACTUAL OR CONSEQUENTIAL WHICH MIGHT RESULT FROM RELIANCE THEREON. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Preferred Deck assumes no obligation or liability for use of this information. NOTICE: PREFERRED DECK MAKES NO WARRANTIES WITH RESPECT TO THIS PRODUCT, EXPRESS OR IMPLIED. PREFERRED DECK DISCLAIMS ALL IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. PREFERRED DECK WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.