



Finish Wax

A High Gloss Finish Wax for Preferred Epoxy

Page 1 of 1

TECHNICAL DATA SHEET

DESCRIPTION AND USE: Preferred Deck's **Finish Wax** is a non-toxic, non-yellowing acrylic floor finish for use on all types of sealed floors. This high gloss wax can easily be maintained by spray buffing. **Finish Wax** provides a brilliantly polished "sacrificial layer" of wax, protecting the sealer underneath. So, this product not only improves the floor's overall appearance, but helps decrease maintenance costs.

CHEMICAL COMPOSITION: Acrylic polymer emulsion, ethylene copolymers, proprietary additives and quality control agents.

COVERAGE RATE: Approximately 1200 sq. ft. per gallon.

CLEAN UP: Soap and water.

SURFACE PREPARATION: Remove other waxes and polishes first with Preferred Deck's **Citra-Peel**. Rinse floor and let dry completely.

APPLICATION RECOMMENDATIONS: Spread **Finish Wax** in a thin even coat over the floor using a lamb's wool applicator or a clean finish mop. Allow to dry completely (approximately 30 minutes.) Apply a second coat and let dry completely. Damp mop with a neutral detergent. Buff regularly to restore the "wet look." Apply **Finish Wax** as needed in order to restore the brilliant gloss. No stripping is necessary before recoating. Up to 10 coats of **Finish Wax** can be applied before stripping is necessary with Preferred Deck's **Citra-Peel**.

SPRAY BUFFING INSTRUCTIONS: Dilute 1 part of **Finish Wax** to 3 parts water. Using a hand sprayer, mist approximately a 10 sq. ft. area and buff with a polishing pad until all liquid disappears and there is a brilliant shine. Repeat this process in sections until the entire floor is waxed.

MAINTENANCE: Occasional mopping with a neutral detergent will maintain the smooth glossy surface. In heavy traffic areas, apply an additional thin coat of **Finish Wax** on a regular basis after mopping and rinsing the floor. Make sure the floor is completely dried before application.

HANDLING PRECAUTIONS: Avoid contact with skin; wear protective gloves. Read Material Safety Data Sheet before using.

WARNING: Harmful if swallowed. Avoid contact with eyes and skin. Goggles and gloves are recommended. Use with adequate ventilation.

FIRST AID: INGESTION: Obtain medical attention at once. EYE CONTACT: Flush with clean water for 15 minutes and obtain medical attention. INHALATION: Remove to fresh air and obtain medical attention. SKIN CONTACT: Wash with soap and water. Obtain medical attention if irritation is severe or persistent.

WARRANTY INFORMATION: Preferred Deck products have a limited two year, non-transferable warranty. This warranty refers to such failures as flaking, peeling, chipping and is limited by the specific items listed below. All warranty issues will be investigated by Preferred Deck with the cooperation of the contractor who installed the product. The end-user may be present during this investigation process, but no investigation will occur directly with the end-user (without the presence of the contractor.) Preferred Deck will not under any circumstance be liable for damages in excess of the purchase price of the products used on the job. Preferred Deck is not liable for consequential or secondary damages resulting from the failure of a warranted item or the failure to provide service due to conditions beyond its control. LIMITATIONS ARE DAMAGES CAUSED BY: 1. The customer due to neglect, abuse, or lack of reasonable care. 2. Settling due to expansive soil, fill dirt movement, drainage, or alkali-silica reaction. 3. Acts of God. 4. Improper installation. All claims must be reported in writing to Preferred Deck within ten days.

DISCLAIMER AND LIMITATION OF LIABILITY

To the best of our knowledge, the information contained herein is accurate. The warranty described herein shall be in lieu of any other warranty, expressed or implied, including but not limited to, any implied warranty of merchantability or fitness for a particular purpose. There are no warranties that extend beyond the description of the face hereof. The Buyer's sole and exclusive remedy against the Seller shall be for the replacement of the products or refund of the purchase price in the event that a defective condition of the products should be found to exist. No other remedy (including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property, or any other incidental or consequential loss) shall be available to the Buyer. The sole purpose of this exclusive remedy shall be to provide Buyer with replacement of the products or refund of the purchase price of the products if any defect in materials or workmanship is found to exist. The exclusive remedy shall not be deemed to have failed its essential purpose so long as the Seller is willing and able to replace the defective products or refund the purchase price. The Buyer must give the Seller notice in writing of any alleged defect covered by this warranty together with all identifying details, including the Product Code(s), description and date of purchase, within thirty (30) days of the discovery of the defect. Final determination of the suitability of the material for the use contemplated, the manner of use, and whether the use infringes any patents, is the sole responsibility of the Buyer. Dispose of unwanted material per federal, state, and local regulations.

FOR PROFESSIONAL USE ONLY. KEEP OUT OF THE REACH OF CHILDREN.

Preferred Deck Systems

7534 W Madison St • Tolleson AZ 85353

888.440.3320 • Fax 623.474.2251 • www.prefdeck.com

MADE IN USA

