



# Super Deck Prep

## A Safe, "Green" Alternative to Acid

Page 1 of 1

### TECHNICAL DATA SHEET

**DESCRIPTION AND USE:** Preferred Deck's **Super Deck Prep** is a safe, "green" alternative to acid washing/etching concrete. Use this deep penetrating cleaner to avoid the hazards associated with muriatic acid. When using **Super Deck Prep**, there is no need to neutralize afterwards. Etching with this product is NOT done with nylogrit brushes (as with acid etching), so two men are not required. **Super Deck Prep** is the best product to use to prepare concrete for epoxy, acid stain, and water-based stain applications.

**Super Deck Prep** is a cleaner and renovator that quickly dissolves lime deposits, scale, rust, mortar, algae and stains from interior and exterior concrete. It also can be used on tile, brick, glass, and aluminum frames.

**CHEMICAL COMPOSITION:** Biodegradable surfactants, inhibitors and acidic boosters.

**COVERAGE RATE:** Approximately 250-300 sq. ft. per gallon when used full strength. Approximately 500-600 sq. ft. per gallon when diluted.

**LIMITATIONS:**

- Some types of stainless steel, chrome plating, porcelain on steel and polished decorative aluminum may discolor.

**Test before using.**

- Do not use on magnesium or zinc (galvanized) items.
- Do not use with Nylon brushes.
- Use with care around landscaping

**APPLICATION RECOMMENDATIONS:** **Super Deck Prep** may be used full strength or diluted with water. Dilution rates will vary; each concrete slab is different. For an acid stain or water-based stain surface preparation, dilute 1 Part **Super Deck Prep** to 3 Parts water. For a hard-troweled surface or to aggressively clean surface for a Preferred Deck acrylic system, dilute 1:1. A second application may be necessary. For a Preferred Epoxy application, use full strength to achieve an 80-100 grit profile.

Apply with a brush, sprayer, or use the dip and roll method. When spraying, use a plastic or polyethylene sprayer and use a very coarse spray-pattern to avoid inhaling the mist. Avoid over-spray. Allow the **Super Deck Prep** solution to soak in for several minutes. Rinse thoroughly with water. When using diluted **Super Deck Prep**, scrub with a stiff broom, then rinse thoroughly with water. Repeat if necessary. For heavily stained or soiled areas, use with a stiff bristle brush and rinse.

**CLEAN UP:** Soap and water.

**HANDLING PRECAUTIONS:** Avoid contact with skin; wear protective gloves. Read Material Safety Data Sheet before using.

**WARNING:** Harmful if swallowed. Avoid contact with eyes and skin. Goggles and gloves are recommended. Use with adequate ventilation.

**FIRST AID:** INGESTION: Obtain medical attention at once. EYE CONTACT: Flush with clean water for 15 minutes and obtain medical attention. INHALATION: Remove to fresh air and obtain medical attention. SKIN CONTACT: Wash with soap and water. Obtain medical attention if irritation is severe or persistent.

**WARRANTY INFORMATION:** Preferred Deck products have a limited two year, non-transferable warranty. This warranty refers to such failures as flaking, peeling, chipping and is limited by the specific items listed below. All warranty issues will be investigated by Preferred Deck with the cooperation of the contractor who installed the product. The end-user may be present during this investigation process, but no investigation will occur directly with the end-user (without the presence of the contractor.) Preferred Deck will not under any circumstance be liable for damages in excess of the purchase price of the products used on the job. Preferred Deck is not liable for consequential or secondary damages resulting from the failure of a warranted item or the failure to provide service due to conditions beyond its control. LIMITATIONS ARE DAMAGES CAUSED BY: 1. The customer due to neglect, abuse, or lack of reasonable care. 2. Settling due to expansive soil, fill dirt movement, drainage, or alkali-silica reaction. 3. Acts of God. 4. Improper installation. All claims must be reported in writing to Preferred Deck within ten days.

**DISCLAIMER AND LIMITATION OF LIABILITY**

To the best of our knowledge, the information contained herein is accurate. The warranty described herein shall be in lieu of any other warranty, expressed or implied including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose. There are no warranties that extend beyond the description of the face hereof. The Buyer's sole and exclusive remedy against the Seller shall be for the replacement of the products or refund of the purchase price in the event that a defective condition of the products should be found to exist. No other remedy (including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property, or any other incidental or consequential loss) shall be available to the Buyer. The sole purpose of this exclusive remedy shall be to provide Buyer with replacement of the products or refund of the purchase price of the products if any defect in materials or workmanship is found to exist. The exclusive remedy shall not be deemed to have failed its essential purpose so long as the Seller is willing and able to replace the defective products or refund the purchase price. The Buyer must give the Seller notice in writing of any alleged defect covered by this warranty together with all identifying details, including the Product Code(s), description and date of purchase, within thirty (30) days of the discovery of the defect. Final determination of the suitability of the material for the use contemplated, the manner of use, and whether the use infringes any patents, is the sole responsibility of the Buyer. Dispose of unwanted material per federal, state, and local regulations.

**FOR PROFESSIONAL USE ONLY. KEEP OUT OF THE REACH OF CHILDREN.**

**Preferred Deck Systems**

**7534 W Madison St • Tolleson AZ 85353**

**888.440.3320 • Fax 623.474.2251 • [www.prefdeck.com](http://www.prefdeck.com)**

**MADE IN USA**

